

RUMBLE
CONCEPT.COM

FENDER ELIMINATOR

RU27965 RU27966

SV650 2003-07 SV1000 2003-10

WWW.RUMBLECONCEPT.COM

info@rumbleconcept.com

TEL: (514) 312-2134

FAX: (514) 312-2092

We at Rumble Concept encourage all installations to be performed by a **PROFESSIONAL**. If you choose to install this product yourself, please read all instructions and take all appropriate safety measures to ensure the proper and safe installation of your new Fender kit.

Before installation: our fender eliminator have been designed for modification purposes, we are not responsible for the use or misuse of any products, or verification of the local department of motor vehicles.

Included:

- 1 X Fender Eliminator Bracket
- 1 X Licence plate light
- 2 X plate screws + nuts

****After any installations or modifications, the fender eliminator not returnable. We are not responsible for any damages to the part during the installation process, or to the bike (including the stock undertail part).**

1. Remove front and rear seat.
2. Gently take off the tail section part.
3. Unplug both signals and license plate light.
4. Unscrew the two 10mm bolts on each side of your stock undertray and then pull it down.

***To hold down your stock undertray you can use the metal rod inside your tail section to create a space between your subframe and stock undertray while installation (see picture A).

5. Remove your stock mudguard and pull the fuse box (keep the rubber part) of the mudguard and relocate it on your new fender eliminator (see picture B)
6. Install your fender eliminator with the 4 stock bolt of your mudguard directly on the subframe.
7. Now remove the metal rod and pry your plastic stock undertray bring it to the right place in to the slot on the new fender eliminator. (see picture C and D)
8. Install your license plate light and signals and make your wire connections .
9. Reinstall your two 10mm bolts ,tail section, seats, make sure everything work's fine.
10. ENJOY THE RIDE.....





WWW.RUMBLECONCEPT.COM

info@rumbleconcept.com

TEL: (514) 312-2134

FAX: (514) 312-2092