



GSXR 600-750 08-10
FENDER ELIMINATOR
RU36414 RU36415

We at Rumble Concept encourage all installations to be performed by a professional. If you choose to install this product, please read all instructions and take all appropriate safety measures to ensure the proper and safe installation of your new fender eliminator.

Before installation:
our fender eliminator have been designed for modification purposes, we are not responsible for the use or misuse of any products, or verification of the local department of motor vehicules.

Included in the kit:

- 1 Fender Eliminator Bracket (3 pcs)
- 1 Licence plate light CY25760
- 4 Sleeve FS36547
- 2 Bolts M6x12mm QU27948
- 2 Lock nuts M6 QU27946
- 2 licence plate screws + nuts



1. Remove the solo seat or rear seat.
2. Remove the left tail section to get access to wiring and unplug the licence plate light.
3. Underneath remove the mudguard with the 4 bolts then replace the 4 sleeves by the ones included see pict A
4. Gently remove the painted tail light plastic cover to have access and pull down the stock undertail to have space to drive plate light connector. see pict B
5. Install both side of your new fender eliminator with the 4 stock bolts
6. Install the mid part of your new fender (plate holder)
7. Drive the plate light wire into the specific hole on the left side and then in the stock hole on the undertail
6. Put back the solo seat or rear seat in place. and enjoy!!!



**For further assistance or information, we may be reached at info@rumbleconcept.com.

**After any installations or modifications, the fender eliminator not returnable. We are not responsible for any damages to the part during the installation process, or to the bike (including the stock undertail part).